



NON-CONTACT INFRARED THERMOMETER now only R999.00 excl VAT R1295 excl VAT

* Medical grade

* 5-years warranty

- * Calibratable
- * CE & ISO 13485 approved
- * Safe & Hygenic (no lazer and disinfectable)
- * 3 Colour display to draw the attention to increased temperature
- * Memory storage facility

TECHNICAL DATA

MATERIAL ABS Plastic COLOR White/ Grey DIMENSION 105 mm (L) x 48 mm (W) x 150 mm (H) WEIGHT 165 g DISPLAY RESOLUTION 0.1°C (0.1°F) FOREHEAD MEASURING RANGE 32 - 42.9°C / 90 - 109.2°F MEASUREMENT DISTANCE Within 5 cm WEASURING ACCURACY Within 35°C - 42°C (± 0.2°C) 95°F - 107.6°F (± 0.4°F) Out of 35°C - 42°C (± 0.3°C) 95°F - 107.6°F (± 0.6°F) OPERATING TEMPERATURE 16 - 35°C / 60.8 - 95°F STORAGE TEMPERATURE -20 - 55°C / -4 - 131°F RELATIVE HUMIDITY ≤ 10 - 93%		
DIMENSION 105 mm (L) x 48 mm (W) x 150 mm (H) WEIGHT 165 g DISPLAY RESOLUTION FOREHEAD MEASURING RANGE MEASUREMENT DISTANCE Within 5 cm Within 35°C - 42°C (± 0.2°C) 95°F - 107.6°F (± 0.4°F) Out of 35°C - 42°C (± 0.3°C) 95°F - 107.6°F (± 0.6°F) OPERATING TEMPERATURE 16 - 35°C / 60.8 - 95°F STORAGE TEMPERATURE PRELATIVE HUMIDITY 105 mm (L) x 48 mm (W) x 150 mm (H) Within 35°C - 40°C (± 0.2°C) 90°F - 109.2°F Within 35°C - 42°C (± 0.2°C) 95°F - 107.6°F (± 0.6°F) OPERATING TEMPERATURE 16 - 35°C / 60.8 - 95°F STORAGE TEMPERATURE ≤ 10 - 93%	MATERIAL	ABS Plastic
WEIGHT 165 g DISPLAY RESOLUTION 0.1°C (0.1°F) FOREHEAD MEASURING RANGE 32 - 42.9°C / 90 - 109.2°F MEASUREMENT DISTANCE Within 5 cm Within 35°C - 42°C (± 0.2°C) 95°F - 107.6°F (± 0.4°F) Out of 35°C - 42°C (± 0.3°C) 95°F - 107.6°F (± 0.6°F) OPERATING TEMPERATURE 16 - 35°C / 60.8 - 95°F STORAGE TEMPERATURE -20 - 55°C / -4 - 131°F RELATIVE HUMIDITY ≤ 10 - 93%	COLOR	White/ Grey
DISPLAY RESOLUTION FOREHEAD MEASURING RANGE MEASUREMENT DISTANCE Within 5 cm Within 35°C - 42°C (± 0.2°C) 95°F - 107.6°F (± 0.4°F) Out of 35°C - 42°C (± 0.3°C) 95°F - 107.6°F (± 0.6°F) OPERATING TEMPERATURE 16 - 35°C / 60.8 - 95°F STORAGE TEMPERATURE PRELATIVE HUMIDITY O.1°C (0.1°F) Within 32°C / 90 - 109.2°F Within 5 cm Fig. 10.2°C Other in the state of the state	DIMENSION	105 mm (L) x 48 mm (W) x 150 mm (H)
RESOLUTION 0.1°C (0.1°F)	WEIGHT	165 g
MEASURING RANGE 32 - 42.9°C / 90 - 109.2°F MEASUREMENT DISTANCE Within 5 cm Within 35°C - 42°C (± 0.2°C) 95°F - 107.6°F (± 0.4°F) Out of 35°C - 42°C (± 0.3°C) 95°F - 107.6°F (± 0.6°F) OPERATING TEMPERATURE 16 - 35°C / 60.8 - 95°F STORAGE TEMPERATURE -20 - 55°C / -4 - 131°F RELATIVE HUMIDITY ≤ 10 - 93%		0.1°C (0.1°F)
DISTANCE Within 35°C - 42°C (± 0.2°C) MEASURING 95°F - 107.6°F (± 0.4°F) Out of 35°C - 42°C (± 0.3°C) 95°F - 107.6°F (± 0.6°F) OPERATING 16 - 35°C / 60.8 - 95°F STORAGE -20 - 55°C / -4 - 131°F RELATIVE ≤ 10 - 93%	MEASURING	32 - 42.9°C / 90 - 109.2°F
MEASURING ACCURACY 95°F − 107.6°F (± 0.4°F) Out of 35°C - 42°C (± 0.3°C) 95°F − 107.6°F (± 0.6°F) OPERATING TEMPERATURE 16 - 35°C / 60.8 − 95°F STORAGE TEMPERATURE -20 - 55°C / -4 - 131°F RELATIVE HUMIDITY ≤ 10 - 93%		Within 5 cm
Out of 35°C - 42°C (± 0.3°C) 95°F - 107.6°F (± 0.6°F) OPERATING TEMPERATURE 16 - 35°C / 60.8 - 95°F STORAGE TEMPERATURE -20 - 55°C / -4 - 131°F RELATIVE HUMIDITY ≤ 10 - 93%		
TEMPERATURE 16 - 35°C / 60.8 - 95°F STORAGE TEMPERATURE -20 - 55°C / -4 - 131°F RELATIVE HUMIDITY ≤ 10 - 93%		
TEMPERATURE -20 - 55°C / -4 - 131°F RELATIVE HUMIDITY ≤ 10 - 93%		16 - 35°C / 60.8 – 95°F
HUMIDITY ≤ 10 - 93%	The second state of the second	-20 - 55°C / -4 - 131°F
BOWER SUBBLY 2 x 1 5 V A A Bottony (Not Included)	District Control of the Control of t	≤ 10 - 93%
POWER SUPPLY 2 x 1.5 v AA Battery (Not included)	POWER SUPPLY	2 x 1.5 V AA Battery (Not Included)
WARRANTY 5 years	WARRANTY	5 years
STANDARD ISO 13485, CE	STANDARD	ISO 13485, CE
PACKAGING 1 each/ box	PACKAGING	1 each/ box



Shipping country wide (T's & C's apply)

For more info call:

JHB: 011 873 1941

CT: 021 552 3646

e-mail: info@melcoinstro.co.za